

SAFETY DATA SHEET (SDS)

INX Products PlastxKleen

Date: 01.01.2015
SDS Number: R0311201
Version: 2.5

INX Products PlastxKleen is sold to distributors (and ultimately end-users), in containers of small volumes. This MSDS has been developed to address safety topics for those handling and using these carefully manufactured and distributed products. All pertinent health, safety and environmental information is presented in this document per the requirements of the U.S. Federal OSHA Hazard Communication Standard (29 CFR 1910.1200) and Canadian WHMIS.

1. PRODUCT AND COMPANY IDENTIFICATION

Product name:	PlastxKleen	INX Products LLC
Product code:	Multiple	4030 Kidron Road, Suite 10
Product Use Description:	Solvent Plastic Cleaner and Adhesive Remover	Lakeland, FL 33811 Emergency Telephone 1-888-646-9830

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance: liquid

WARNING! FLAMMABLE LIQUID AND VAPOR. MAY BE HARMFUL IF INHALED. MAY BE FATAL IF SWALLOWED. MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION. PROLONGED OR REPEATED CONTACT MAY DRY SKIN, CAUSE IRRITATION AND BURNS.

Health Flammability Reactivity Other

HMIS 2 2 0

NFPA 3 3 0

Potential Health Effects

Routes of exposure

Inhalation, Skin absorption, Skin contact, Eye Contact, Ingestion

Eye contact

Can cause eye irritation. Symptoms include stinging, tearing, redness, and swelling of eyes.

Skin contact

Can cause skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, and drying and cracking of skin, burns and other skin damage.

Ingestion

This material can get into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury.

Inhalation

Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (see Section 8.).

Aggravated Medical Condition

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material:., Skin, lung (for example, asthma-like conditions), Liver, kidney

Symptoms

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:., stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness), difficulty in breathing, Bloody urine, blood abnormalities (breakage of red blood cells), kidney damage, liver damage, coma

Target Organs

Acute lethal exposure to ethylene glycol monobutyl ether in animal studies has resulted in congestion of organs including kidney, spleen, and lung., Exposure to this material (or a component) has been found to cause kidney damage in male rats. The mechanism by which this toxicity occurs is specific to the male rat and the kidney effects are not expected to occur in humans., Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals:., mild, reversible liver effects, mild, reversible spleen effects, blood abnormalities

Carcinogenicity

This material is not listed as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), or the Occupational Safety and Health Administration (OSHA). Ethylene glycol monobutyl

SAFETY DATA SHEET (SDS)

INX Products PlastxKleen

Date: 01.01.2015
SDS Number: R0311201
Version: 2.5

ether has been shown to cause cancer in laboratory animals. The relevance of this finding to humans is uncertain.

Reproductive hazard

This material (or a component) has been shown to cause harm to the fetus in laboratory animal studies. Harm to the fetus occurs only at exposure levels that harm the pregnant animal. The relevance of these findings to humans is uncertain.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.
LIGHT ALIPHATIC DISTILLATE	64742-89-8 >=60-<70%
Glycol Ether Blend	Proprietary >=15-<20%

4. FIRST AID MEASURES

Eyes

If symptoms develop, immediately move individual away from exposure and into fresh air. Flush eyes gently with water for at least 15 minutes while holding eyelids apart; seek immediate medical attention.

Skin

Remove contaminated clothing. Flush exposed area with large amounts of water. If skin is damaged, seek immediate medical attention. If skin is not damaged and symptoms persist, seek medical attention. Launder clothing before reuse.

Ingestion

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

Notes to physician

Hazards: Inhalation of high concentrations of this material, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this material. This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity (See Section 2 - Swallowing) when deciding whether to induce vomiting.

Treatment: No information available.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Dry chemical, Carbon dioxide (CO₂)

Hazardous combustion products

carbon dioxide and carbon monoxide, hydrocarbons

Precautions for fire-fighting

Material is volatile and readily gives off vapors which may travel along the ground or be moved by ventilation and ignited by pilot lights, flames, sparks, heaters, smoking, electric motors, static discharge or other ignition sources at locations near the material handling point. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively. Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA). Water may be ineffective for extinguishment unless used under favorable conditions by experienced fire fighters. Use water spray to cool fire exposed containers and structures until fire is out if it can be done with minimal risk. Avoid spreading burning liquid with water used for cooling purposes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

For personal protection see section 8. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

SAFETY DATA SHEET (SDS)

INX Products PlastxKleen

Date: 01.01.2015
SDS Number: R0311201
Version: 2.5

Environmental precautions

Prevent spreading over a wide area (e.g. by containment or oil barriers). Do not let product enter drains. Do not flush into surface water or sanitary sewer system. Local authorities should be advised if significant spillages cannot be contained.

Methods for cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

Other information

Comply with all applicable federal, state, and local regulations. Suppress (knock down) gases/vapours/mists with a water spray jet.

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. Static ignition hazard can result from handling and use. Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Special precautions may be necessary to dissipate static electricity for non-conductive containers. Use proper bonding and grounding during product transfer as described in National Fire Protection Association document NFPA 77.

Storage

Store in a cool, dry, ventilated area, away from incompatible substances.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Light Aliphatic Distillate (Petroleum) 64742-89-8

OSHA Z1 time weighted avg 500ppm

AGGIH time weighted avg 300ppm

OSHA Z1 time weighted avg 52,000 mg/m³

OSHA Z1 time weighted avg 1,370 mg/m³

HEXYLENE GLYCOL 107-41-5

ACGIH Ceiling Limit Value: 25 ppm

NIOSH Ceiling Limit Value and Time Period (if specified): 25 ppm

NIOSH Ceiling Limit Value and Time Period (if specified): 125 mg/m³

ETHYLENE GLYCOL

MONOBUTYL ETHER

111-76-2

ACGIH time weighted average 20 ppm

NIOSH Recommended exposure limit(REL):5 ppm

NIOSH Recommended exposure limit(REL):24 mg/m³

OSHA Z1 Permissible exposure limit 50 ppm

OSHA Z1 Permissible exposure limit 240 mg/m³

General advice

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

Exposure controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Eye protection

Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.

Skin and body protection

SAFETY DATA SHEET (SDS)

INX Products PlastxKleen

Date: 01.01.2015
SDS Number: R0311201
Version: 2.5

Wear normal work clothing including long pants, long-sleeved shirts and foot covering to prevent direct contact of the product with the skin. Launder clothing before reuse. If skin irritation develops, contact your facility health and safety professional or your local safety equipment supplier to determine the proper personal protective equipment for your use. Wear resistant gloves (consult your safety equipment supplier).

Respiratory protection

A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by air-purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state Liquid

Color Clear

Odor Light Solvent

Boiling point No data

pH No data

Flash point 70 °F / 20 °C, Tag closed cup

Evaporation rate >1 (Ethyl Ether)

Explosion limits No data

Vapor pressure >1, 16.00 hPa @ 68 °F / 20 °C

Vapor density (>) 1 (AIR=1)

Density 0.8 g/cm³ @ 77.00 °F / 25.00 °C

6.61 lb/gal @ 77.00 °F / 25.00 °C

Solubility Negligible

10. STABILITY AND REACTIVITY

Stability

Stable.

Conditions to avoid

Avoid heat, open flame, and prolonged storage at elevated temperatures., Avoid contact with: Exposure to moisture.

Incompatible products

Acids, aluminum, strong alkalis, strong bases, salts of strong bases, strong oxidizing agents, strong reducing agents

Hazardous decomposition products

carbon dioxide and carbon monoxide, hydrocarbons, aldehydes, ketones, Organic acids

Hazardous reactions

Product will not undergo hazardous polymerization.

Thermal decomposition No data

11. TOXICOLOGICAL INFORMATION

Acute oral toxicity

LIGHT ALIPHATIC DISTILLATE LD 50 Rat: > 8,000 mg/kg

HEXYLENE GLYCOL LD 50 Rat: 3,700 mg/kg

ETHYLENE GLYCOL MONOBUTYL ETHER LD 50 Guinea pig: 1,200 mg/kg

Acute inhalation toxicity

LIGHT ALIPHATIC DISTILLATE LC 50 Rat: 3400 ppm, 4 h

HEXYLENE GLYCOL LC 50 Rat: > 18000 ppm, 8 h

ETHYLENE GLYCOL MONOBUTYL ETHER LC 50 Guinea pig: > 633 ppm, 1 h

Acute dermal toxicity

LIGHT ALIPHATIC DISTILLATE LD 50 Rat: > 4,000 mg/kg

HEXYLENE GLYCOL LD 50 Rabbit: 12,300 mg/kg

ETHYLENE GLYCOL MONOBUTYL ETHER LD 50 Guinea pig: > 2,000 mg/kg

SAFETY DATA SHEET (SDS)

INX Products PlastxKleen

Date: 01.01.2015
SDS Number: R0311201
Version: 2.5

12. ECOLOGICAL INFORMATION

Aquatic toxicity

Acute and Prolonged Toxicity to Fish No data available

Acute Toxicity to Aquatic Invertebrates No data available

Environmental fate and pathways No data available

13. DISPOSAL CONSIDERATIONS

Waste disposal methods

Dispose of in accordance with all applicable local, state and federal regulations.

14. TRANSPORT INFORMATION

Ground Package Shipping: < 1 Liter (.94/gallon) container can be properly shipped via standard ground service, ORM-D

USDOT Proper Shipping Name: Paint Related Material (Naphtha), 3-Flammable, UN1263, PGII

IMDG, IATA_P, IATA_C, CFR_RAIL, CFR_INWTR: Paint Related Material (Naphtha), 3-Flammable, UN1263, PGII

15. REGULATORY INFORMATION

California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth, or any other reproductive defects.

SARA Hazard Classification Fire Hazard, Acute Health Hazard

SARA 313 Component(s)

ETHYLENE GLYCOL

MONOBUTYL ETHER

111-76-2 >15%

Reportable quantity - Components

LIGHT ALIPHATIC DISTILLATE 64742-89-8 none

HEXYLENE GLYCOL 107-41-5 none

ETHYLENE GLYCOL MONOBUTYL ETHER 111-76-2 none

Notification Status

EU.	EINECS	y (positive listing)
US.	Toxic Substances Control Act	y (positive listing)
Canada.	Canadian Environmental Protection Act CEPA	y (positive listing)
	Domestic Substances List (Can. Gaz. Part II, Vol133)	y (positive listing)

Reportable Quantity – Product

US. EPA (40 CFR 302) @15295 lbs

Xylene 1330-20-7 @100lbs

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

SDS Date: 01.01.2015 SDS Number: R0311201 Version: 2.5